



Delayed Coking Operational Optimization

Jesus R. Cabello
Technical Service Director

REFCOMM
RIO DE JANEIRO

29 Sept – 3 Oct 2014

Coking
.com

Delayed Coking Operational Optimization

Foster Wheeler Delayed Coking Best Practices

- FW employs a three prong approach
 1. Design details
 2. Operational techniques
 3. Operating instructions and training
- Most recommendations are good practice regardless of type of coke produced





Enclosed Slide Valve Bottom Unheading System

Courtesy of Delta Valve

Delayed Coking Operational Optimization

Design Details Heaters

- Use of 6-pass double fired coker heaters for larger coke drum module capacities and 3-pass double fired coker heaters for smaller drum module capacities.
- Continually developing new burner technology for lower NO_x and optimal flame pattern
- Better on-line spalling procedures; more effective and efficient resulting in increased run lengths. On-line pigging also possible.
- Over 5 years run length between turnarounds
- Fully modularized design for lower installed cost.




More reliable and environmentally friendlier operation

Delayed Coking Operational Optimization

Design Details Fractionator


- Water wash systems
- Wash oil spray chamber
- Fractionator bottom fines removal



Delayed Coking Operational Optimization

Design Details Coke Drums


- Single thickness drum wall
- Optimized crotch radius for weld build up hot box cone/straight wall detail
- Integral forged ring skirt design on cone/ straight wall detail
- Use of anchor bolts with disk spring allows base plate flexibility



Delayed Coking Operational Optimization

Design Details Blowdown System

- Shed deck trays vs. disc and donut trays
- External steam heater
- Vent Gas recovery
- Wax tailings / Slop backwash to quench



Easier to operate and maintain

Delayed Coking Operational Optimization

Design Details

- Operating station – enclosed, ventilated, line of sight.
- Remote top and bottom unheading
- Remote coke cutting
- Multiple safe & protected egress options with fire barriers
- Water sprays
- Safety interlocks on cutting system
- Drill stem guides
- Top slide valve unheading device, with enclosure for cutting tool
- Coke drum nuclear level detector located to ensure water fill




Safer to operate

Delayed Coking Operational Optimization

Design Details

Total Automation of Coke Drum Operations



Delayed Coking Operational Optimization

Fouling Causes

- Feedstock
 - High sodium
 - High asphaltenes
 - Incompatible crude blends
- Coker Heater
 - Low velocity in tubes
 - Low velocity injection media rate and/or wrong location
 - Excessive temperatures (crossover and/or COT)
 - Poor burner operation
- Coker Fractionator
 - Low overhead temperatures → salting
 - High bottoms temperatures → coking (rare, typically seen with HHCGO product operations)

Delayed Coking Operational Optimization

Fouling Prevention/Mitigation

- Feedstock
 - Minimize injection of caustic downstream of desalter
 - Ensure crude is well desalted
 - High softening point feeds may need diluent
 - Add aromatic feedstock (slurry / decant oil) to heavy oil residues to dilute fouling properties
 - Limit feedstock sodium to 10 wppm max (15 wppm max peaks)
 - Test feed blends for compatibility
- Coker Heater
 - Double-fired
 - Longer run lengths if processing heavy feeds
 - On-line spalling more effective
 - Better temperature control with individual convection sections
 - Off-line decoking: steam-air, pigging

Delayed Coking Operational Optimization

Fouling Prevention/Mitigation

- Coker Fractionator

Salting

- Provide water wash system at the top of the tower
- Increase overhead product endpoint

Coking

- External quench for HHCGO product draw

Delayed Coking Operational Optimization

Operational Techniques *Furnace Fouling*

Fouling and coking will occur; The best chance to control it is to monitor the heater operations:

- Fouling Monitoring
 - Heater Skin Temperatures
 - Firing Rate (Fuel Consumption)
 - Oxygen
 - Velocity Media
- Process feed changes
 - Rate
 - Quality
- Draft
- O₂
- Burner monitoring
- Firing rate/inlet temperature – fouling of upstream exchangers
- Prepare for the eventual decoking operation and use the method best for your situation

Delayed Coking Operational Optimization

Operational Techniques *Furnace Media Injection Rates* *Fact or Fiction*

- Never too much steam / condensate injection
- The rate is fixed and does not have to be varied
- Do not need to change injection locations
- Steam or condensate. It does not matter.
- **Fiction:** Especially with Condensate. It overloads the firing and pumps. No benefits
- **Fiction:** As the feed drops the injection, medium must increase to maintain velocities
- **Fact:** Unless the pumps are at capacity all the injection medium at heater inlet is preferred
- **Fact:** But for spalling condensate is the preferred medium

Delayed Coking Operational Optimization

Operational Techniques Furnace Draft Control

- Draft should be measured under the first row of convection tubes
- High Draft causes more air leakage and lowers the heater's efficiency, the higher the draft higher the leakage.
- High draft changes the burner flame pattern-longer flames.
- High draft can cause a heater to be firing/flue gas limited.
- Low draft could mean a positive and dangerous fire box, especially the sight doors




Figure 15—Typical Draft Profile in a Natural Draft Heater

Delayed Coking Operational Optimization

Operational Techniques *Furnace Burner Issues*

- Poor flame pattern
 - Draft too high or too low?
 - O₂ too high or too low?
 - Burner registers opened/closed?
 - Burner tips plugged?
 - Considerably different fuels?
 - High fuel pressure?
 - Flame impingement?
 - Burners shut off?
 - Air temperature from preheater



Delayed Coking Operational Optimization

Operational Techniques

Coke Drum Quench to Minimize Hot Spots

- Completely fill with water to about 3 meters above coke bed
- Use slow, optimized quench ramp rate based on experience
- 1/2 to 1 hour soak time
- Track quench and blowdown system water flows to verify that the coke drum is flooded with water
- Maintain controlled back pressure



Delayed Coking Operational Optimization

Operational Techniques *Dynamic Manipulation*

- Increase heater outlet temperature 2 to 3 °C for final 2 hrs before switch
- Switch techniques: maintain forward flow (steam downstream of SP-6)
- Hold switch valve at midpoint for 15 mins during drum switch
- Switch from steamout to quench: continue steam until water enters drum (calculated value)



Delayed Coking Operational Optimization

Operating Instructions Shot Coke Management

- Attention to audible & light alarms during structure operations
- All non-essential personnel to be off drum structure
- Do not unhead top until drum is vented & drained
- Be alert for telltales of possible hot spots



Delayed Coking Operational Optimization

Operating Instructions

- Remain in shelter when the cutting system is pressurized
- Ensure sufficient positive forward flow of steam and/or water as feed is switched
- Use safety precautions when blowing the transfer line clean with steam
- Cutting operators to verify that coke handling operators are notified that coke will be exiting from the coke chute



Delayed Coking Operational Optimization

Causes of Foaming

- Sudden depressurization of drums
- Inadequate heating / early switch / short cycle time
- Low Coker Heater coil outlet temperature (COT)
 - High fouling tendency or high VCM coke operations
 - Sudden shutdown of burners and relighting
- High velocity in drums
 - Higher feed rate / lower coking pressure
 - Excessive velocity medium / steam purges
- Suspected feedstock
 - High solid / fines content
 - High paraffinic feeds – cracks quicker than aromatic feeds
 - High sodium feeds – can increase the rate of cracking / rate of gas going through the liquids in the drum

Delayed Coking Operational Optimization

Foaming Prevention/Mitigation

- Design
 - Provide adequate Coke Drum outage
 - Provide adequate Coke Drum diameter (make note of maximum vapor velocity limit)
 - Provide adequate number and type of Coke Drum level detectors
- Operation
 - Optimize antifoam injection –
 - Reduce unit feed rate to reduce vapor velocity in drum
 - Increase Coker Heater coil outlet temperature (COT)
 - Increase/introduce aromatic feed
 - Increase recycle → reduces foam height since recycle is aromatic
 - Add decant oil → lowers feed blend paraffinicity, viscosity, and surface tension but not enough to do away with silicone injection

Delayed Coking Operational Optimization

Foaming


FW Guidelines for Antifoam Injection

- FW guidelines for injection rates and flows
 - 50% injection at 2 hours before switch / 80% of gamma level range
 - 100% injection at 80% of gamma level range
 - Continue injection until steamout to Blowdown operation and Coke Drum pressure has stabilized

Delayed Coking Operational Optimization

Cycle Time Optimization - Minimizing Thermal Stress

- Long slow quench ramp
- Automated quench programs (step versus ramp)
- Maximize preheat (minimum coke drum skin temperature)
- Coke drum TI monitoring program
 - Additional 32 TI's
 - Monitor gradient (coking & quench)
 - Monitor max temperature differential



Delayed Coking Operational Optimization

Cycle Time Optimization

- Unheading
 - Manual (more time required than automatic)
 - Automatic
 - Remote operation
- Automated Cutting Systems
 - Vendor supplied (Flowserve and Ruhrpumpen)
- Pressure Test
 - 15 minutes minimum even with slide valves
 - Ensures that water vaporized from drum walls during depressure
 - Minimize water going to coke condensate and blowdown
 - Too much water may lead to pump cavitation
- Drum Switch

Delayed Coking Operational Optimization

Maximization of Distillate Yields

- Coker yields are dependent on feedstock quality, operating conditions, recycle, and cycle time
- Several operational procedures are available to optimize the unit during the coking cycle
- Addition of aromatic feed can be beneficial in some cases
- Additive study applications are still in development

Delayed Coking Operational Optimization

Maximization of Distillate Yields

- Crude type / source
- Feedstock quality
 - TBP cutpoint / distillation
 - API gravity
 - Viscosity
 - Concarbon Residue (CCR)
 - Asphaltenes (heptane insolubules / HIS)
 - Sulfur
 - Nitrogen
 - Metals / ash
- Operating conditions
- Coking cycle time

Delayed Coking Operational Optimization

Effect of Operating Conditions *Rules of Thumb*


- Process Variables
 - Temperature Higher is better
 - Pressure Lower is better
 - Recycle Lower is better, but...



- Lower recycle increases HCGO
 - End point
 - CCR
 - Heptane insolubles (nC7 asphaltenes)
 - Metals (Ni + V)

Delayed Coking Operational Optimization

Impact of Recycle on Yield Distribution



Delayed Coking Operational Optimization

Effect of Coking Cycle Time *Rules of Thumb*

- Range: 12 – 24 hours for fuel grade cokers
- Typical: 18 hours for new, fuel grade cokers
- Usually set by refinery operational capabilities and requirements
- Can use shorter cycles, e.g. 12 hours, for revamp designs to allow for processing more feed capacity
 - Additional stress on Coke Drum
 - Tendency to reduce Coke Drum life

Delayed Coking Operational Optimization

Optimization During Coking Cycle

- Reaction rates need to be increased using increased temperature to account for limited reaction time; prevents hot spots
 - Ramp up COT by 2 – 3°C, 2 hours before switch
 - Bring COT back to normal, 1 hour after switch
- Coker Fractionator swings during Coke Drum switch and preheat
 - Increase total draw product pan levels
 - Increase HCGO PA temperature (PA steam generator duty varied)
 - Leave switch valve in midpoint position for 15 minutes to minimize heat loss
- Coke Drum Quench
 - Ramp schedule / adequate quench time
 - Water level above coke bed with 30 minute soak
 - Thermal monitoring

Delayed Coking Operational Optimization

Optimization During Coking Cycle

- Coke Drum Level Detectors
 - Continuous gamma ray – only detects fluid at a level
 - Nuclear point density detector (neutron backscatter / NBS) – can distinguish between coke, foam, and water
 - FW typical design:
 - One nuclear point (density) detector 0.6 m (2 ft) below TTL (cuts off quench water pump on high pressure)
 - One nuclear point (density) mid point between normal coke bed height and TTL (alarm for water fill during quench)
 - Continuous level to cover coke bed height 2 hrs before switch to mid point between normal coke bed height and TTL
 - Bottom nuclear point (density) detector at 25% fill (coke volume)

Delayed Coking Operational Optimization

Coke Morphology

- Shot
 - High asphaltene feedstock
 - Low pressure / low recycle
 - Max liquid / min coke yields
 - $CCR / nC7 < 2$
 - 30-50 HGI
 - Fuel grade
- Sponge
 - Low asphaltene feedstock
 - High pressure / moderate recycle
 - Lower liquid / higher coke yield
 - 40-70 (Hvy) / 70-100 (Lt) HGI
 - Fuel / anode grade



Delayed Coking Operational Optimization

Coke Morphology

- Needle
 - Low asphaltene feedstock / aromatic tar
 - Very high pressure / high recycle
 - 70-110 HGI
 - Coke production operation
 - Electric grade
- “Rules of Thumb” (Fuel Grade)
 - Raise COT 2.8 – 3.9 °C in final hours of coking or for 1% decrease in VCM
 - Raise COT 0.6 – 1.1 °C for one hour reduction in coking cycle time



Delayed Coking Operational Optimization

Training

- KnowledgeWeb Plus on line training program for Foster Wheeler Delayed Coking Technology is an efficient tool to improve on-boarding of new hires and up-skill existing workers in DCU safety and operations
 - 24/7 Real time access anywhere, anytime with the internet and a browser
 - Customized: Unit / Site Specific
 - Helps to maximize yields by applying the knowledge of the unit designers
 - Helps to improve reliability by incorporating the knowledge and maintenance procedures of the different process equipment.



www.fwc.com